

First Place Portable Race Clock Assembly Instructions

(Two-person setup recommended)

1. Pull tripod legs apart to open it.



2. Get down on one knee. With one hand holding one tripod leg on the ground, place your other hand on the main tripod pole and pull it upward to get the tripod to the desired height.
3. Tighten the height adjustment knob at the base of the tripod. Turn until snug, but do not over-tighten.
4. Raise the inner pole of the tripod until you see the first height adjustment hole.



5. Insert the silver pin thru the front side and the back side of the height adjustment holes.



6. Lower the inner pole until the silver pin is resting on the plastic where the inner pole and main pole meet.



7. Tighten the height adjustment knob. Turn until snug, but do not over-tighten.

8. Locate the mounting plate and the oblong knob bolt.



9. With the flat side up, place the mounting plate onto the top of the inner pole. (This may take several tries as the fit is very snug.)



8. Screw the oblong knob bolt into the front of the mounting plate to secure the mounting plate to the inner pole. Turn until snug, but do not over-tighten.



10. Locate the two holes on the bottom edge of the clock.



11. Place the clock onto the mounting plate with the bottom edge holes lined up with the slots of the mounting plate. Have the 2nd person hold the clock in place.



Mounting Plate Slots

12. With the 2nd person holding the clock, you will be able to see if the holes are lined up properly by looking up from the bottom of the mounting plate.

Disregard
corner
holes



Clock Holes

13. Have a 2nd person hold/steady the clock onto the mounting plate.



14. Locate the two small knob bolts and place a washer on them.



15. Secure the clock to the mounting plate by screwing the knob bolt thru the mounting plate into the bottom edge holes of the clock. Turn until snug, but do not over-tighten.



16. Set-up complete.

